



## MATERIAL SAFETY DATA SHEET

MSDS Number: 2404E

### Section 1 PRODUCT AND COMPANY IDENTIFICATION

Trade Name: UNI-WELD PRIME TITE BLUE PRIMER NSF LISTED  
 Product Nos.: 8056S, 8046S, 8036S, 8024  
 Product Use: Primer for PVC and CPVC Plastic Pipe  
 Formula: See section 2  
 Synonyms: Plastic Pipe Primer  
 Firm Name & Address: United Elchem Industries UNITED ELCHEM IND. c/o OATEY CO. 4700 West 160th Street, P.O. Box 35906 Cleveland, Ohio 44135  
 www.elchem.com  
 Firm Phone No:  
 Emergency Phone Nos.: For Emergency First Aid call 1-877-740-5015. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.  
 Prepared by: Technical Department  
 Preparation Date: 11/01/2009

### Section 2 HAZARDS IDENTIFICATION

Emergency Overview:

Blue

liquid with sharp, penetrating odor. Extremely flammable liquid and vapor. Vapors may cause flash fire. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects. Swallowing may cause irritation, nausea, vomiting, diarrhea and kidney or liver disorders. Aspiration hazard. May be fatal if swallowed. Symptoms may be delayed.

### Section 3 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:	%wt/wt :	CAS NUMBER:	ACGIH TLV TWA:	OSHA PEL TWA	OTHER:
Tetrahydrofuran	20 - 40%	109-99-9	50 ppm(skin) 100 ppm STEL	200 ppm	25 ppm (Mfg)
Methyl Ethyl Ketone	35 - 50%	78-93-3	200 ppm 300 ppm	200 ppm	None
Acetone	25 - 40%	67-64-1	500 ppm 750 ppm STEL	1000 ppm	None

OSHA Hazard Classification: Flammable, irritant, organ effects

### Section 4 FIRST AID MEASURES

Skin: Remove contaminated clothing immediately. Wash all exposed areas with soap and water. Get medical attention if irritation develops. Remove dried cement with Oatey Plumber's Hand Cleaner or baby oil.  
 Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.  
 Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.  
 Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

**Section 5 FIRE FIGHTING MEASURES**  
Flashpoint / Method: 14 - 23 Degrees F. (-10 to -5 Degrees C) / CCCFP  
Flammability: LEL = 1.8 % Volume, UEL = 11.8 % Volume  
Extinguishing Media: Use dry chemical, CO2, or foam to extinguish fire. Cool fire exposed container with water. Water may be ineffective as an extinguishing agent.  
Special Fire Fighting Procedure: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored  
Unusual Fire And Explosion Hazards: Extremely flammable liquid. Keep away from heat and all sources of ignition including sparks, flames, lighted cigarettes and pilot lights. Containers may rupture or explode in the heat of a fire. Vapors are heavier than air and may travel to a remote ignition source and flash back.  
Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

**Section 6 ACCIDENTAL RELEASE MEASURES**  
Spill or Leak Procedures: Remove all sources of ignition and ventilate area. Stop leak if it can be done without risk. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up spill with an inert absorbent such as sand, earth or other non-combusting material. Put absorbent material in covered, labeled metal containers. Prevent liquid from entering watercourses, sewers and natural waterways. Report releases to authorities as required. See Section 13 for disposal information.

**Section 7 HANDLING AND STORAGE**  
Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation (equivalent to outdoors). Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.  
Storage: Store in a cool, dry, well-ventilated area away from incompatible materials. Keep containers closed when not in use.  
Other: "Empty" containers retain product residue and can be hazardous. Follow all MSDS precautions in handling empty containers. Do not cut or weld on or near empty or full containers.

**Section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**  
Ventilation: Open doors & windows. Provide ventilation capable of maintaining emissions at the point of use below recommended exposure limits. If used in enclosed area, use exhaust fans. Exhaust fans should be explosion-proof or set up in a way that flammable concentrations of solvent vapors are not exposed to electrical fixtures or hot surfaces.  
Respiratory Protection: For operations where the exposure limit may be exceeded, a NIOSH approved organic vapor respirator or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.  
Skin Protection: Rubber gloves are suitable for normal use of the product. For long exposures chemical resistant gloves may be required such as 4H(tm) or Silver Shield(tm) to avoid prolonged skin contact.  
Eye Protection: Safety glasses with side shields or safety goggles.

**Section 9 PHYSICAL AND CHEMICAL PROPERTIES**  
Boiling Point: 151 Degrees F / 66 Degrees C  
Melting Point: Not applicable  
Vapor Pressure: 145 mmHg @ 20 Degrees C  
Vapor Density: (Air = 1) 2.5

Volatile Components: 99.96%  
Solubility In Water: Negligible  
pH: Not applicable  
Specific Gravity: 0.83 +/- 0.02 @ 20 Degrees C  
Evaporation Rate: (BUAC = 1) = 5.5 - 8.0  
Appearance: Blue  
Odor: Ether-Like  
Will Dissolve In: Tetrahydrofuran  
Material Is: Liquid

**Section 10 STABILITY AND REACTIVITY**

Stability: Stable.  
Conditions To Avoid: Avoid heat, sparks, flames and other sources of ignition.  
Hazardous Decomposition: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.  
Products:  
Incompatibility/ Materials To Avoid: Oxidizing agents, alkalis, amines, ammonia, acids, chlorine compounds, chlorinated inorganics (potassium, calcium and sodium hypochlorite) and hydrogen peroxides. May attack plastic, resins and rubber.  
Hazardous Polymerization: Will not occur.

**Section 11 TOXICOLOGICAL INFORMATION**

Inhalation: Vapors or mists may cause mucous membrane and respiratory irritation, coughing, headache, dizziness, dullness, nausea, shortness of breath and vomiting. High concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.  
Skin: May cause irritation with redness, itching and pain. Methyl ethyl ketone may be absorbed through the skin causing effects similar to those listed under inhalation.  
Eye: Vapors may cause irritation. Direct contact may cause irritation with redness, stinging and tearing of the eyes. May cause eye damage.  
Ingestion: Swallowing may cause abdominal pain, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.  
Chronic Toxicity: Prolonged or repeated overexposure cause dermatitis and damage to the kidney, liver, lungs and central nervous system.  
Toxicity Data: Acetone: Oral rat LD50: 5,800 mg/kg  
Inhalation rat LC50: 50,100 mg/m3/8 hours  
Methyl Ethyl Ketone: Oral rat LD50: 2,737 mg/kg  
Inhalation rat LC50: 23,500 mg/m3/8 hours  
Skin rabbit LD50: 6,480 mg/kg  
Sensitization: None of the components are known to cause sensitization.  
Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.  
Mutagenicity: Acetone, methyl ethyl ketone are generally thought not to be mutagenic.  
Reproductive Toxicity: Methyl ethyl ketone has been shown to cause embryofetal toxicity and birth defects in laboratory animals. Acetone has been found to cause adverse developmental effects only when exposure levels cause other toxic effects to the mother.  
Medical Conditions Aggravated By Exposure: Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.

**Section 12 ECOLOGICAL INFORMATION**

This product is not expected to be toxic to aquatic organisms.  
Acetone: 96 hour LC50 for fish is greater than 100 mg/L.  
Methyl Ethyl Ketone: 96 hour LC50 for fish is greater than 100 mg/L.  
VOC This product emits VOC's (volatile organic compounds) in its use. Make sure

Information: that use of this product complies with local VOC emission regulations, where they exist.  
VOC Level: Maximum 550 g/L per SCAQMD Test Method 316A.

**Section 13 DISPOSAL CONSIDERATIONS**

Waste Disposal: Dispose in accordance with current local, state and federal regulations.  
RCRA Hazardous Waste U002, U159  
Number:  
EPA Hazardous Waste D001, D035, F003, F0005  
ID Number:  
EPA Hazard Waste Ignitable Waste. Toxic Waste (Methyl Ethyl Ketone content)  
Number:

**Section 14 TRANSPORT INFORMATION**

DOT	<u>Less than 1 Liter (0.3 gal)</u>	<u>Greater than 1 Liter (0.3 gal)</u>
UN/NA Number:	None	UN1993
Proper Shipping Name:	Consumer Commodity	Flammable Liquid, NOS (Methyl Ethyl Ketone, Acetone)
Hazard Class:	ORM-D	3
Packing Group:	None	PGII
Hazard Labels:	None	Flammable Liquid
IMDG		
UN Number:	UN1993	UN1993
Proper Shipping Name:	Flammable Liquid, NOS (Limited Quantity)	Flammable Liquid, NOS (Methyl Ethyl Ketone, Acetone)
Hazard Class:	3	3
Packing Group:	II	II
Label:	None (Limited Quantities are expected from labeling)	Class 3 (Flammable Liquid)
Flashpoint (deg C)	-10 to -5 Degrees C	-10 to -5 Degrees C

2008 North American Emergency Response Guidebook Number: 127

**Section 15 REGULATORY INFORMATION**

Hazard Category for Acute Health, Chronic Health, Flammable  
Section 311/312:

Section 302 This product does not contain chemicals regulated under SARA Section 302. Extremely Hazardous Substances (TPQ):  
Section 313 Toxic Chemicals: This product does not contain chemicals subject to SARA Title III Section 313 Reporting requirements.  
CERCLA 103 Reportable Quantity: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Tetrahydrofuran (40% maximum) of 1,000 lbs, is 2,500 lbs.  
Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.  
California Proposition 65: This product does not contain any chemicals subject to California Proposition 65 regulations.  
TSCA Inventory Canadian WHIMS Classification: All of the components of this product are listed on the TSCA inventory. Class B, Division 2; Class D, Division 2, Subdivision B; Class D, Division 2, Subdivision A. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**Section 16****OTHER INFORMATION**

NFPA and HMIS:

NFPA Hazard Signal: Health: 2 Flammability: 3 Reactivity: 1 Special: None

HMIS Hazard Signal: Health: 2\* Flammability: 3 Reactivity: 1 PPE: G

**Disclaimer:**

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.

Template: tmpl-us-e3